

Track Drive Power Buggy

The WTB-16 models feature an aggressive track pattern, enabling the buggy to travel effortlessly through soft soils and muddy site conditions. The

WTB-16 is engineered with top quality components and built with the attention to detail that has made MQ Whiteman the leader in motorized buggies.

Both models feature polyethylene tubs. The WTB-16PD includes a pivot dump tub, while the WTB-16 has a standard straight dump tub.



WTB-16PD
Pivot dump tub
16 cu.ft. capacity



WTB-16
Straight dump tub
16 cu.ft. capacity

- **Innovative WTB-16PD model** features a pivot dump tub capable of rotating up to 180 degrees, to easily and precisely deliver material. Hand and foot controls facilitate tub rotation and dumping control.
- **Optimal traction and durability** assured by a steel imbedded ladder track design
- **Rugged undercarriage guide wheels** are ductile cast iron
- **Low maintenance hydraulic design** eliminates wear parts such as belt-drives and drive couplers
- **High torque drive motors** propel the buggy through tough conditions and offer fail-safe braking
- **Versatile tub offers 16 ft.³ (2,500 LB.) capacity** and polyethylene construction for easy cleaning

- **Narrow width** allows the buggy to pass through doorways or confined areas
- **Travel efficiently around the site** with speeds of 5.1 MPH unloaded and 4.7 MPH loaded
- **Easy steering dual control levers** allow the operator to control the unit while minimizing fatigue
- **Powerful and reliable Honda GX690 engine** produces 22 horsepower
- **Long run times** are achieved with 5 gallon capacity fuel tank



Features — Track Drive Power Buggy



Dual control handles provide consistent tracking, easy steering, and minimized operator fatigue. (WTB-16 shown)



Hand and foot controls facilitate tub rotating and dumping. (WTB-16PD shown)



100% hydraulic drive — No V belts, pulleys, clutches or mechanical gear reductions.



Front panel raises to provide complete service access.



Aggressive tack pattern for use in soft soil to muddy site conditions.



Premier high torque Poclain hydraulic motors feature fail-safe brakes.



Folding foot plate allows operator to walk behind machine when used in confined areas. Perforated platform prevents material build up.

Specifications — Standard Power Buggies

Models	WBH-16F	WBH-16EF	WBH-16EAWDF	WBH-21EF	WTB-16	WTB-16PD
Tire Type	Foam fill	Foam fill	Foam fill	Foam fill	Track	Track
Wheelbase — in. (cm)	43 (109.2)	43 (109.2)	43 (109.2)	43 (109.2)	N/A	N/A
Width — Standard Dual Wheels in. (cm) (Track)	44 (111.7)	44 (111.7)	44 (111.7)	44 (111.7)	35.5 (90.2)	35.5 (90.2)
Width — Outer wheels removed	30.75 (78.10)	30.75 (78.10)	30.75 (78.10)	N/A	N/A	N/A
Length with foot plate extended — in. (cm)	103 (261.6)	103 (261.6)	103 (261.6)	103 (261.6)	90.5 (229.9)	110.2 (280)
Height — in. (cm)	51 (129.5)	51 (129.5)	51 (129.5)	51 (129.5)	56.5 (143.5)	55.6 (141.2)
Weight — lb. (kg)	1351 (612.8)	1363 (618.2)	1493 (677.2)	1492 (676.7)	1896 (860)	2138 (970)
Max. Load — Dual Wheels Lb. (kg)	2500 (1133.8)	2500 (1133.8)	2500 (1133.8)	3200 (1451)	2500 (1134)	2500 (1134)
Max. Load — Outer Wheels removed — lb. (kg)	1000 (453)	1000 (453)	1000 (453)	N/A	N/A	N/A
Capacity CF. (Cu. mter)	16 (0.453)	16 (0.453)	16 (0.453)	21 (0.590)	16 (0.453)	16 (0.453)
Tub Discharge Direction	Straight dump	Straight dump	Straight dump	Straight dump	Straight dump	Pivot dump up to 180°
Engine	Honda 11.9 HP (8.8kW)	Honda 11.9 HP (8.8kW)	Vanguard 18 HP (13.4kW)	Vanguard 18 HP (13.4kW)	Honda 22 HP (16.4kW)	Honda 22 HP (16.4kW)
Starting System	Recoil	Recoil and Electric	Recoil and Electric	Recoil and Electric	Electric	Electric
Fuel capacity — gal. (lt)	4.8 (18.1)	4.8 (18.1)	4.8 (18.1)	4.8 (18.1)	5 (18.9)	5 (18.9)
Travel speed — mph (km)	7.25 (11.6)	7.25 (11.6)	7.25 (11.6) Standard 5.3 (8.52) Traction assist 6.3 (10.13) AWD	7.25 (11.6)	5.1 (8.2) Empty 4.7 (7.6) Loaded	5.1 (8.2) Empty 4.7 (7.6) Loaded
Bucket Material	Polyethylene	Polyethylene	Polyethylene	Polyethylene	Polyethylene	Polyethylene
Gradeability	Max. 10% (6 degree)	Max. 10% (6 degree)	Max. 10% (6 degree)	Max. 10% (6 degree)	Uphill Max. 20% (10 degree) Side Max. 10% (6 degree)	Uphill Max. 20% (10 degree) Side Max. 10% (6 degree)

Specifications — TuffTruk

Models	TB12SE	TB11G	TB12PE	TB11PG
Tire type	Pneumatic	Pneumatic	Pneumatic	Pneumatic
Wheel base in.	28.6	29.5	28.6	29.5
Width in.	33.4	34.5	33.4	34.5
Length in.	70.3	68.5	70.3	68.5
Height in.	41.9	38	41.9	38
Weight lb.	529	396	529	396
Maximum payload capacity lb.	1,100	990	1,100	990
Capacity ft³	12.0	10.6	12.0	10.6
Power Source	Two DC brushless motors 750W / 24V	Honda GX200 5.5 HP Gas Engine	Two DC brushless motors 750W / 24V	Honda GX200 5.5 HP Gas Engine
Battery type	2x12 volt AGM deep cell batteries	N/A	2x12 volt AGM deep cell batteries	N/A
Starting system	Electric	Manual recoil	Electric	Manual recoil
Drive and controls	4x4 - 24 volt motor	4x4 - Hydrostatic system	4x4 - 24 volt motor	4x4 - Hydrostatic system
Fuel capacity gal. (liter)	None	0.682 (3.1)	None	0.682 (3.1)
Travel speed forward - mph	0 to 3.5	0 to 4	0 to 3.5	0 to 4
Travel speed reverse - mph	0 to 1.5	0 to 1.5	0 to 1.5	0 to 1.5
Bucket material	Steel	Steel	Polyethylene	Polyethylene
Gradability	45%	45%	45%	45%
Oscillation	9°	6°	9°	6°
Articulation	40°	40°	40°	40°
Noise level dBa	76	96	76	96

Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. Multiquip Inc. and its subsidiary companies makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any

responsibility or liability of any kind whatsoever with respect to the accuracy of the engine power rating. Users are advised to consult the engine manufacturer's owners manual and its website for specific information regarding the engine power rating.

**Your trusted
partner for
over 45 years**

